

	Model	Cutting Width	Hydraulic Flow	Cutting Diameter	Motor Type	Drive Type	Tip Speed	Max PSI Rating (PSI cont./int.)	Blade Carrier Type	Blades	Deck Thickness	Chain Curtain(s)	Weight
STANDARD-DUTY	4200X	42 in	8-20 GPM	3 in	Geroler-style hydraulic	Right-angle gearbox	6,500-16,200 ft/min	3,000/3,500	1" GRD-50 disc	(2) 0.5 x 4 in; updraft	10-ga (.135 in)	Both sides	690 lbs
	4800X LF	48 in	8-15 GPM	3 in	Geroler-style hydraulic	Right-angle gearbox	7,500-14,000 ft/min	3,000/3,500	1" GRD-50 disc	(2) 0.5 x 4 in; updraft	7-ga (.188 in)	Both sides	860 lbs
	4800X SF	48 in	16-25 GPM	4 in	Geroler-style hydraulic	Right-angle gearbox	11,750-18,400 ft/min	3,000/3,500	1" GRD-50 disc	(2) 0.5 x 4 in; updraft	7-ga (.188 in)	Both sides	860 lbs
	4800X HF	48 in	26-40 GPM	5 in	Geroler-style hydraulic	Right-angle gearbox	7,500-11,600 ft/min	3,000/4,100	1" GRD-50 disc	(2) 0.5 x 4 in; updraft	7-ga (.188 in)	Both sides	860 lbs
HEAVY-DUTY	42X HD	42 in	14-20 GPM	4 in	Radial piston hydraulic	Direct drive	9,500-13,500 ft/min	3,500	1" GRD-50 disc	(2) 0.5 x 4 in; updraft	10-ga (.135 in)	Optional/Removable	750 lbs
	42X XP	42 in	21-29 GPM	5 in	Radial piston hydraulic	Direct drive	10,200-14,200 ft/min	3,500	1" GRD-50 disc	(2) 0.5 x 4 in; updraft	10-ga (.135 in)	Optional/Removable	750 lbs
	48X HD	48 in	17-29 GPM	5 in	Radial piston hydraulic	Direct drive	9,500-16,300 ft/min	3,500	1" GRD-50 disc	(2) 0.5 x 4 in; updraft	7-ga (.188 in)	Optional/Removable	800 lbs
	48X XP	48 in	30-37 GPM	6 in	Radial piston hydraulic	Direct drive	8,600-10,600 ft/min	3,500	1" GRD-50 disc	(2) 0.5 x 4 in; updraft	7-ga (.188 in)	Optional/Removable	800 lbs
FULL-SIZE HEAVY-DUTY	60X HD	60 in	20-32 GPM	10 in	Radial piston hydraulic	Direct drive	9,500-15,100 ft/min	4,000	1" GRD-50 disc OR two-piece 5/8" steel discs	(3) drop-blades: 0.625 x 5"; non-updraft OR (4) flat-blades: 0.625 x 5.188"; non-updraft	1/4 in	Optional/Removable	1,940 lbs
	60X XP	60 in	33-45 GPM	10 in	Radial piston hydraulic	Direct drive	12,200-16,600 ft/min	4,000	1" GRD-50 disc OR two-piece 5/8" steel discs		1/4 in	Optional/Removable	1,940 lbs
	72X HD	72 in	20-32 GPM	10 in	Radial piston hydraulic	Direct drive	10,300-14,300 ft/min	4,000	1" GRD-50 disc OR two-piece 5/8" steel discs	(3) drop-blades: 0.625 x 5"; non-updraft OR (4) flat-blades: 0.625 x 5.188"; non-updraft	1/4 in	Optional/Removable	2,330 lbs
	72X XP	72 in	33-45 GPM	10 in	Radial piston hydraulic	Direct drive	13,200-18,000 ft/min	4,000	1" GRD-50 disc OR two-piece 5/8" steel discs		1/4 in	Optional/Removable	2,330 lbs