

		Model	Cutting Width	Hydraulic Flow	Max Cut	Motor Type	Drive Type	Motor Protection	Tip Speed	Max PSI Rating	Blade Carrier Type	Blades	Deck Thickness	Chain Curtain(s)	Weight
CLOSED FRONT	COMPACT	4200	42 in	8-20 GPM	2 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	6,500-16,200 ft/min	3,000/3,500	1" GRD-50 plate	(2) 14.75 x 4 x 0.5 in; updraft	10-ga (.135 in)	Front; rear	470 lbs
		4800 LF	48 in	8-15 GPM	3 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	7,500-14,000 ft/min	3,000/3,500	1" GRD-50 plate	(2) 14.75 x 4 x 0.5 in; updraft	7-ga (.188 in)	Front; rear	672 lbs
		4800 SF	48 in	16-25 GPM	4 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	11,750-18,400 ft/min	3,000/3,500	1" GRD-50 plate	(2) 14.75 x 4 x 0.5 in; updraft	7-ga (.188 in)	Front; rear	690 lbs
OPEN FRONT	COMPACT	4201	42 in	8-20 GPM	2 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	6,500-16,200 ft/min	3,000/3,500	1" GRD-50 plate	(2) 14.75 x 4 x 0.5 in; updraft	10-ga (.135 in)	Rear	470 lbs
		4801 LF	48 in	8-15 GPM	3 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	7,500-14,000 ft/min	3,000/3,500	1" GRD-50 plate	(2) 14.75 x 4 x 0.5 in; updraft	7-ga (.188 in)	Rear	672 lbs
		4801 SF	48 in	16-25 GPM	4 in	Geroler-style hydraulic	Right-angle gearbox	Pressure relief valves, GRD-2 shear bolt	11,750-18,400 ft/min	3,000/3,500	1" GRD-50 plate	(2) 14.75 x 4 x 0.5 in; updraft	7-ga (.188 in)	Rear	690 lbs