



INTRODUCES

THE 72 & 78 OPEN FRONT BRUSH CUTTERS

LEADS THE PACK IN POWER AND PERFORMANCE

DIRECT DRIVE - PISTON MOTOR



INDUSTRY LEADING WARRANTY ON ALL BRUSHWOLF MODELS

New Brush Wolf 72 & 78 inch Open Front Brush Cutters

The Industry asked and we answered.....

Introducing the New 72 and 78 inch Open Front brush cutters from Cross-Tech Manufacturing.

The 72 and 78 inch cutters come in two models – The HD/O line with auxillary hydraulic flows rated at 23 to 29 GPM and the XP/O line with auxillary hydraulic flows rated at 30 to 40 GPM.

This work horse is designed for industrial and commercial applications. You can rely on the new open front 72 and 78 models to consistently tackle heavy brush and trees up to 8 inches in diameter. The Brush Wolf 72 and 78 Open Front cutters make clearing brush efficient and quick – improving your ROI and increasing your profit.

The hydraulic piston motor provides quick recovery time with less bogging when accelerating through thick brush. Tip speed and torque are optimum for efficient cutting. The massive 1 inch blade carrier is CNC balanced and true - and contains 3 blades. The New Brush Wolf 72 and 78 Open Front Cutters performance and reliability is unmatched.

The open front and V-Notch” design allows for increased operator precision cutting of trees and saplings. A deflector plate has been added to control discharged material from the front deck – providing increased protection for people and structures nearby. A vented hood shields the drive train and hydraulic connections from impacts and debris. Abrasion resistant AR 400 skid pads provide extended life to the ground engaging skid rails. The deck design allows material to glide off during operation preventing unwanted build up of chips and debris. Hydraulic hoses are guarded with heavy duty spiral hose wrap to stave off entanglements from branches and keep you cutting. Dust caps come standard on all quick couplers to ensure longer motor life and reduced contamination.

Our 3 year warranty on structural steel and 18 months on the hydraulic motor is the best in the industry.

SPECIFICATIONS

Operating Equipment: Skid Steer Loader

Max Cutting Capacity: 8”

Cutting Width: 72 & 78”

Auxiliary Hydraulic Flow HD/O: 23-29 GPM

Auxiliary Hydraulic Flow XP/O: 30-40 GPM

Weight: 1494 to 1610 lbs

Overall Length: 72”

Overall Width: 75.250”

Overall Length: 78”

Overall Width: 81.250”

Deck Thickness: .250”

Blades: (3) .625” x 5.000” (High Strength) - Standard

Blade Carrier Type: (1) 1.000” Disc - Standard

Blade Rotation: Counter Clockwise

Motor Protection: Pressure Reliefs, Case Drain

Operating PSI Cont./Int.: 4000

Hydraulic Hose with Protective Wrap: Standard 114”

(Custom lengths available upon request)



Toll Free: 877.390.9857
33877 Gendreau Road
Crosslake, MN 56442
sales@brushwolf.com
www.brushwolf.com

