

SUPER M-AX* FOR SITE PREP TRACTORS

*PATENT PENDING

144A Model - 12'



Increase revenue and productivity clearing land, plantations, pipelines, power lines, right-of-way's, and roadway easements with options available in 12 feet or 16 feet wide.

- 144A estimate of 3.87 acres @ 3 MPH, and the 192A an estimate of 5.24 acres @ 3 MPH (speed will depend upon density).
- Shut-off sensor on the 192A when hydraulic wings are raised 15 degrees.
- The 192A has two hydraulic retractable wings that lift for transport and provide the flexibility to maneuver through your landscape.
- The flat blades are reversible and are three times the strength of mild steel.
- Cuts trees up to 8" in diameter – dependent upon type of wood and the vegetation density.
- Technician provided at your preferred location for set-up.

192A Flex Wing Model - 16'*



192A - Two hydraulic retractable wings adjust for transport and your environment*



SPECIFICATIONS	144A**	192A**
Cutting Width:	144.000	186.750
Overall Width:	149.500	192.000
Overall Length:	125.000	127.000
Cutting Capacity:	8"	8"
Blade Carrier Type-Discs:	(2) .625 GRD-50 High Strength	(3) .625 GRD-50 High Strength
Reversible Flat Blades: (3x strength of mild steel)	(8) 5.188 x 17.750 x .625 (High Strength)	Center Only (4) 5.188 x 17.750 x .625 (High Strength)
Reversible Wing Flat Blades: 192A Only:	N/A	(8) 5.188 x 14.250 x .625
Wing Pin Size (Greaseable)	N/A	1.000
Blade Rotation:	Counter Clockwise	Counter Clockwise
Motor Protection:	Pressure Relief	Pressure Relief
Deck Thickness:	.313 GRD-50 One Piece of Formed Steel	
Hydraulic Hose: (Bundled, Spiral Guard)***:	STANDARD	
Coupling***:	STANDARD	
Bearing Housing Shaft Size:	3.750	3.750
Cylinder Size:	N/A	3.500 Bore, 2.000 Rod, 16.000 Stroke
Required GPM:	42 - 58	65 - 85
PSI MAX:	5000	5000

All high flow models include a case drain to relieve excess pressure build-up and protect hydraulic motor life. *Custom fit to each machine.